



VISION Rechargeable Products
Sealed Lead Acid Battery

www.vision-batt.com

FM Series

General purpose application

VISION FM series are designed for general purpose applications, such as UPS, telecom, electrical utilities.

With 10 years design life, the batteries comply to the most popular international standards, such as IEC896-2, BS6290-4, Eurobat Guide.

The battery container and cover are available both in V0 class flame retardant ABS or HBO ABS plastics.

Shenzhen Center Power Tech Co., Ltd. has come to obtain wide recognition from customers all over the world. This is not only due to the fact that our products are featured by reliable stability in quality, but also because we attach great importance to our communication with customers and our perfect understanding of customers' requirements as well.

Shenzhen Center Power Tech. Co., Ltd

6FM120-X 12V 120 Ah

(Edition June 2004)

General Features

- Positive and negative plates in lead-calcium-tin alloy
- Stable Quality & High Reliability
- Sealed Construction
- Long Service Life
- Maintenance-Free Operation
- Low Pressure Venting System
- Low Self Discharge
- U. L. Component Recognition
- Six months shelf life at 20°C
- Design life 10 years



Dimensions and Weight

	SI Units	English Units
Length	410mm	16.1inch
Width	176mm	6.93inch
Height	227mm	8.94inch
Total Height	227mm	8.94inch
Approx. Weight	38.0Kg	83.8lbs

Performance Characteristics

- Nominal Voltage 12V
- Number of cell 6
- Nominal Capacity 77°F(25°C)
 - 10 hour rate (12.0A, 10.8V) 120Ah
 - 5 hour rate (20.0A, 10.5V) 100Ah
 - 1 hour rate (71.6A, 9.60V) 71.6Ah
- Internal Resistance
 - Fully Charged battery 77°F(25°C) 4.3mOhms
- Self-Discharge
 - 3% of capacity declined per month at 20°C(average)
- Operating Temperature Range
 - Discharge -20~60°C
 - Charge -10~60°C
 - Storage -20~60°C
- Max. Discharge Current 77°F(25°C) 950A(5s)
- Short Circuit Current 2250A
- Charge Methods: Constant Voltage Charge 77°F(25°C)
 - Cycle use 14.4-14.7V
 - Maximum charging current 36A
 - Temperature compensation -30mV/°C
- Standby use 13.6-13.8V
 - Temperature compensation -20mV/°C



Center Power Industrial Park, Tongfu Industrial District Dapeng Town, 518120 Shenzhen, China
Tel: 86 755 84318088 Fax: 86 755 84318038 E-mail: sales@vision-batt.com
Website: <http://www.vision-batt.com>

**VISION**VISION Rechargeable Products
Sealed Lead Acid Battery

www.vision-batt.com

(Edition June 2004)

6FM120-X 12V 120Ah**Discharge Data****Constant Current Discharge Data (Amperes at 25°C)**

End Voltage Per cell / V	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60	343	250	196	158	135	120	106	95.8	87.7	81.3	76.0	71.6	51.8	41.9	36.0	32.0	25.1	21.0	18.2	16.2	14.6	13.4	12.5	10.5	5.54
1.65	329	245	195	156	132	116	103	93.6	86.1	80.1	75.2	71.1	51.3	41.4	35.5	31.5	24.9	21.0	18.1	16.0	14.5	13.3	12.3	10.5	5.47
1.70	303	223	187	150	127	112	99.9	90.9	83.8	78.2	73.5	69.7	50.4	40.7	34.9	31.0	24.5	20.7	17.8	15.8	14.2	13.1	12.2	10.4	5.39
1.75	277	210	179	144	122	108	96.4	87.8	81.0	75.6	71.2	67.5	49.0	39.8	34.2	30.5	24.0	20.0	17.3	15.4	14.0	12.9	12.1	10.3	5.31
1.80	253	197	167	137	118	106	94.4	85.7	78.9	73.5	69.1	65.4	46.8	37.4	31.8	28.1	22.6	19.3	16.8	15.0	13.6	12.6	12.0	10.2	5.24

Constant Power Discharge Data (Watts per cell at 25°C)

End Voltage Per cell / V	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1h	1.5h	2h	2.5h	3h	4h	5h	6h	7h	8h	9h	10h	12h	24h
1.60	603	449	370	299	256	227	204	186	172	160	149	141	100	79.6	67.3	59.2	46.9	39.5	34.1	30.3	27.4	25.1	23.3	21.0	11.0
1.65	567	426	358	289	248	220	199	183	171	158	147	137	97.0	76.8	64.7	56.6	45.5	38.9	33.7	29.9	27.1	24.9	23.2	20.1	10.8
1.70	530	404	346	280	240	213	189	171	157	147	138	131	93.0	74.0	62.6	55.0	44.6	38.3	33.2	29.6	26.8	24.7	23.0	19.7	10.6
1.75	494	383	334	270	232	206	184	167	154	143	135	128	91.0	72.6	61.5	54.1	43.7	37.4	32.5	29.1	26.5	24.4	22.8	19.3	10.4
1.80	466	358	310	254	221	199	178	162	150	140	131	124	88.6	70.8	60.1	53.0	43.0	37.0	32.1	28.6	26.0	23.9	22.3	19.0	10.2

Performance drawings